

เครื่องถ่ายเอกสารสี

Standard Features

- Copy / Print / Send / Store
- Color / Black and White
- Print up to 55 ppm (BW),51 ppm Color);letter
- Maximum paper size: 12" x 18"
- 5,000-Sheet Maximum Capacity
- Scan Up to 120/120 ipm Simplex-pass Duplex
- Flexible in-line finishing Options
- Scan directly to Microsoft Word,PowerPoint and Searchable PDF formats
- Hard Disk Drive lock and Erase,Ipsec

office Solutions :

Multifunction printer

Compact design

Color / Black and White





- **Type** : เครื่องถ่ายเอกสาร ระบบดิจิทัลมัลติฟังก์ชัน สี - ขาวดำ
- **Functions** : Print, Copy, Scan, Send and Optional Fax
- **หน้าจอ** : 8.4 SVGA Full-Color TFT Screen
- **ความเร็วการพิมพ์หรือถ่ายเอกสาร** : A4 (ขาว-ดำ / สี): 50 / 45 หน้าต่อนาที , A3 (ขาว-ดำ / สี): 28 / 26 หน้าต่อนาที
- **ความละเอียด** : Reading : 600dpi x 600dpi , Copying : 600dpi x 600dpi
Printing : 1200dpi x 1200dpi (text/line only) , Scan : 600 x 600dpi
- **ความเร็วการประมวลผล** : Canon Custom Processor, 1.2GHz (Uses Main Unit CPU)
- **หน่วยความจำ (Memory)** : Standard: 2GB RAM Maximum: 2.5GB RAM
- **หน่วยเก็บข้อมูล (Hard Disk)** : Standard 160GB (Available Disk Space: 10GB)
Maximum 1TB (Available Disk Space: 115GB)
- **เวลาในการอุ่นเครื่อง** : 31 วินาที
- **ความเร็วการถ่ายสำเนาแผ่นแรก** : ขาว-ดำ: 3.9 วินาที , สี : 6.0 วินาที
- **พิมพ์สองหน้า** : ถ่ายเอกสาร กลับสำเนาหน้า-หลัง ได้อัตโนมัติ
- **ความจุถาดกระดาษ** : ขนาดกระดาษสูงสุด : A3 , ถาดกระดาษมาตรฐาน 550 แผ่น x 2 ถาด (80 แกรม)
ถาดกระดาษเสริม 550 แผ่น x 2 ถาด (80 แกรม) , Paper Deck 2,700 แผ่น (80 แกรม)
สแต็คบายพาส : 100 แผ่น (80 แกรม) , ความจุทั้งหมด: 5,000 แผ่น
- **ขนาดกระดาษ** : Cassette: 305 x 457mm, A3, A4, A4R, A5R, B4, B5, B5R
Custom Size 139.7 x 182mm to 304.8 x 457.2mm
Optional Envelope Feeder, No.10 (COM10), Monarch
DL, ISO-C5, Stack Bypass: A5R - SRA3 (320 x 450mm)
Envelopes, Custom Size 99 x 140mm to 320 x 457mm
- **Media Weight** : Cassette:52 to 220gsm, Stack Bypass:52 to 256gsm
- **จำนวนการถ่ายเอกสารต่อเนื่อง** : สูงสุด 1 ถึง 999 แผ่น
- **อัตรากำลังขยาย** : Zoom 25 - 400 % in 1 % increments
- **ประเภทเครื่องสแกน** : Pull: Network TWAIN Driver
(75 to 600dpi 24bit color/8bit grayscale/2bit Black & White)
- **รูปแบบไฟล์เอาต์พุต** : TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b,
Optimize PDF for Web
- **Address Book Capacity** : LDAP, Local (Max.1800)
- **การเชื่อมต่อเครือข่าย** : (1000BaseT/100Base-TX/10Base-T), (IEEE802.11b/g,
Optional), Protocol: TCP/IP (LPD/Port9100/WSD/IPP/IPPS/SMB/FTP),
IPv6, IPX/SPX (NDS, Bindery), AppleTalk
- **OS Compatibility** : Windows 2000/XP/Server2003/Vista/Server2008/Win7
- **Power Supply** : Voltage: 220-240V AC, Frequency: 50/60Hz
- **คุณสมบัติขั้นสูง** : เครื่องอ่านภาพสี, เครื่องอ่านแท็บลอสซ์, กระดาษสำหรับยูนิต์-2,
อุปกรณ์เย็บเล่มที่เย็บเล่ม, ตัวเข้าเล่มหนังสือเล่มเล็ก
- **การใช้พลังงาน** : 1.8kW max
- **Interface** : USB2.0
- **ขนาดและน้ำหนัก** : 950 x 620 x 715 มิลลิเมตร , น้ำหนักประมาณ 153 กิโลกรัม

Specifications

Main unit			
Operation Panel	8.4" SVGA Full-Color TFT Screen		
Memory	Standard	2GB RAM	
	Maximum	2.5GB RAM	
Hard Disk Drive	Standard	160GB	
	Maximum	1TB	
Network Interface Connection	Standard	1000Base-T/100Base-TX/10Base-T	
	Optional	Wireless LAN (IEEE 802.1x via third-party adapter)	
Other Interface	Standard	USB 2.0 (Host) x 2, USB 2.0 (Device)	
	Optional	Device Port [USB 2.0 (Host) x 2], Serial Interface	
		Copy Control Interface	
Copy/Print Speed (BW/Color, Letter)	C5255	Up to 55/51 ppm	
	C5250	Up to 50/45 ppm	
	C5240	Up to 40/35 ppm	
	C5235	Up to 35/30 ppm	
First-Copy-Out Time (Letter)	C5255/C5250 : BW: 3.9 Seconds, Color: 6.0 Seconds		
	C5240/C5235 : BW: 5.4 Seconds, Color: 8.1 Seconds		
Paper Sources (20 lb. Bond)	Standard:	Dual 550-sheet Paper Cassettes, 100-sheet Stack Bypass	
		Maximum	5,000 Sheets
	Maximum	3,250 Sheets (w/Staple Finisher or Booklet Finisher)	
Output Paper Capacity (20 lb. Bond)	Standard	250 Sheets (Inner Tray)	
	Maximum	3,250 Sheets (w/Staple Finisher or Booklet Finisher)	
Output Paper Sizes	Cassettes	12" x 18",* 11" x 17",* Legal, Letter, Letter-R, Statement-R, Executive, Custom Size (5-1/2" x 7-1/8" to 12" x 18")	
		Bypass	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18")
			Paper Deck
	Other	Envelope Feeder Attachment (COM10 No.10,	
	Options	Monarch, DL, ISO-C5),** Tab Feeding Attachment Kit**	
	Acceptable Paper Weights	Cassettes	14 lb. Bond to 80 lb. Cover (52 to 220 g/m2)
Bypass		14 lb. Bond to 140 lb. Index (52 to 256 g/m2)	
Warm-up Time	C5255/C5250 From Power On: 31 Seconds, From Sleep: 18 Seconds Quick Startup Mode: 7 Seconds***		
	C5240/C5235 From Power On: 31 Seconds, From Sleep: 15 Seconds Quick Startup Mode: 7 Seconds***		
Power Requirements/Plug	C5255/C5250	120V AC, 60Hz, 20A/NEMA 5-20P	
	C5240/C5235	120V AC, 60Hz, 15A/NEMA 5-15P	
Dimensions (H x W x D)	C5255/C5250	37-3/8" x 24-3/8" x 28-1/8" (950mmx620mmx715mm)	
	C5240/C5235	36-5/8" x 24-3/8" x 28" (931mmx620mmx712mm)	
Installation Space (W x D)	C5255/C5250	33-1/2" x 28-1/8" (850mm x 715mm)	
	C5240/C5235	33-1/2" x 28" (850mm x 712mm)	
Weight	C5255/C5250	Approx. 346 lb. (157kg)	
	C5240/C5235	Approx. 333 lb. (151kg)	
Toner (Estimated Yield @ 5% Coverage)	C5255/C5250	Black: 44,000 Images, Color (C,M,Y): 38,000 Images	
	C5240/C5235	Black: 36,000 Images, Color (C,M,Y): 27,000 Images	

Document Feeder		
Scan Method	C5255/C5250	Single-Pass Duplexing, Automatic Document Feeder
	C5240/C5235	Duplex Automatic Document Feeder
Acceptable Originals	Paper Size	11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R
		Scan Speed (BW/Color, Letter)
Paper Capacity (20 lb. Bond)	C5255/C5250	150 Sheets
	C5240/C5235	100 Sheets
Print Specifications		
Engine Resolution	1200 x 1200 dpi	
PDL Support	Standard	UFR II
	Optional	PCL 5c, PCL 6, Adobe PS 3
Print Driver Supported OS	UFR II, PCL 5c/6, Adobe PS 3	Windows® (XP/Windows Vista®/7/8), Windows Server (2003/2008 2008 R2/SBS 2011/2012), Windows Terminal Servers, Microsoft® Clustering Server, Citrix, Macintosh® (OS X 10.5.8 or later, UFR II and PS 3 only), VMware, SAP (PS and PCL Only)
	Direct Print Support	Standard: TIFF, JPEG Optional: PDF, XPS†††, EPS††††
Universal Send Specifications		
Sending Method	E-Mail, I-Fax, File Server (FTP, SMB, WebDAV), Mail Box, Super G3 Fax (Opt.)	
	Communication Protocol	File: FTP (TCP/IP), SMB (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3, I-FAX (Simple, Full)
File Format	Standard	TIFF, JPEG, PDF, PDF (Compact), PDF (Searchable PDF/Apply Policy) PDF (Optimize for Web), PDF/XPS (OCR), PDF/A-1b, XPS, XPS (Compact), OOXML (OCR) (.pptx and .docx)
		Optional
Fax Specifications		
Maximum Number of Connection Lines	4	
Modem Speed	Super G3	33.6 Kbps
	G3	14.4 Kbps
Compression Method	MH, MR, MMR, JBIG	
Sending/Recording Size	Statement to 11" x 17"	
Store Specifications		
Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes	
	Advanced Box	Available
Supported		Protocol: SMB or WebDAV Client PC: Windows® (Windows 2000/XP/Windows Vista®/7)
Memory Media	Standard	USB Memory
	Optional	SD, SDHC, CompactFlash, Memory Stick, Microdrive